

IMAGE FORMING APPARATUS HAVING
TRANSFER BIAS CONTROL FUNCTION

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to an image forming apparatus such as a copying machine, a printer and a facsimile machine and, in particular, to an image forming apparatus having a function of
10 transferring an image formed on an image bearing member to a recording material and thereafter fixing the image thereon.

Related Art

An electrophotographic image forming apparatus
15 is an example of such an image forming apparatus. With the electrophotographic image forming apparatus, an unfixed toner image corresponding to target image information is formed and born on an image bearing member such as an electrophotographic photosensitive
20 body by an image forming process using a heat-fixing visualizing agent (toner). The toner image is transferred by a transferring apparatus from the image bearing member onto a recording material, and the recording material having undergone the transfer
25 of the toner image is introduced into a heating apparatus (heat-fixing apparatus), whereby the toner image is subject to a heat-fixing treatment as a

20032156 022002

permanently fixed image to be discharged as an image formed object (copy, print).

As the transferring apparatus used in such an image forming apparatus, a transferring apparatus of
5 a non-contacting electrostatic transfer method is often used according to the recent tendency to eliminate ozone. The transferring apparatus of the non-contacting electrostatic transfer method is for
10 applying a predetermined transfer bias from a power source to a transfer member such as a transfer roller located on a back side of a recording material, thereby attracting a toner image from an image bearing member with an electric force and transferring it onto the recording material.

15 As a heating apparatus for heat-fixing a toner image on a recording material, a heating apparatus is generally used which brings a pressurizing roller having elasticity in pressed contact with a rotational heating member having a built-in heat
20 source such as a fixing roller or a fixing film and introduces a recording material to its press-contacting nip portion to perform a fixing operation of the toner image.

A pressurizing roller as a pressurizing member
25 used in the above-mentioned heating apparatus is often provided with a heat-resistant elastic body such as silicone rubber on a core metal, which is a

20250220 15:08:10

supporting body and has rigidity and further,
provided with a fluorocarbon resin layer with high
releasing property as a surface layer, if necessary.
The heat-resistant elastic body is required for its
5 function as a part constituting the rotational
heating member and the press-contacting nip portion.
The surface layer may be provided for the purpose of
improving releasing property in order to avoid stains
when adhesion and deposition of dirty toner or
10 recording material components caused by offset or the
like on the side of the rotational heating member are
serious on the surface of the pressurizing roller.

However, a rubber material or a resin material,
which is generally used as an elastic layer or a
15 surface layer, is often an insulator. Thus, when
dried paper with a high electric resistance as a
recording material is passed through the pressurizing
roller, the surface of the pressurizing roller is
charged negatively due to friction with the paper.
20 If toner held on the paper at this point is
negatively charged toner, the toner repulses a
triboelectrification potential of the surface of the
pressurizing roller, resulting in a scattered image
or an offset image.

25 A pressurizing roller is proposed in which a
conductive material is dispersed in a rubber material
or a resin material used for an elastic layer or a

10032155.022602

surface layer and treatment for lowering resistance is applied to the elastic layer or the surface layer in order to avoid such triboelectrification on the surface of the pressurizing roller. A resistance of one or more of these layers is reduced to 10^{13} Ω/sq or less in terms of a surface resistance or 10^{11} Ωcm or less in terms of a volume resistance. The layers with a reduced resistance are electrically grounded, whereby triboelectrification of the surface of the pressurizing roller can be prevented.

However, when an OHT (overhead transfer: a transparent recording sheet for an overhead projector) is used as a recording material to be passed through an apparatus provided with a pressurizing roller (conductive pressurizing roller) which has been subject to treatment for lowering resistance as described above, charges on the back of the OHT, which the pressurizing roller contacts, may flow to the ground to offset an image on the surface of the OHT.

In general, an OHT is made of a PET (polyethylene terephthalate) sheet coated with a surface-active agent or the like on its surface. Therefore, it has high insulating property in its thickness direction, but has a lower surface resistance. Due to such a condenser construction, if negatively charged toner is used, the OHT is subject

to a positive transfer bias on its back when passing through a transfer portion. At this point, negative charges are induced on the surface of the OHT. In this state, the negative charges electrostatically balance with positive charges on the back of the OHT. However, if the OHT contacts a pressurizing roller, which has been subject to treatment for lowering resistance when passing through a fixing nip, the positive charges (transfer charges) on the entire back of the OHT flow to the ground. Thus, the front of the OHT is largely occupied by the negative charges and the negatively charged toner repulses the negative charges to have a weaker holding force, resulting in an offset image.

Further, when a recording material is plain paper, since it has lower insulating property in its thickness direction and a higher surface resistance in comparison with the OHT, such an offset image does not occur.

20

SUMMARY OF THE INVENTION

The present invention has been devised in view of the above-mentioned drawbacks, and it is an object of the present invention to provide an image forming apparatus that can suppress offset of an image.

It is another object of the present invention to provide an image forming apparatus that can suppress

10082156 "022602"

offset of an image regardless of a type of a recording material.

It is still another object of the present invention to provide an image forming apparatus that
5 can suppress offset of an image even if a resin sheet is passed through fixing means provided with a pressurizing roller having a low resistance layer.

It is yet still another object of the present invention to provide an image forming apparatus
10 including: an image bearing member; a transfer member for transferring an image from the image bearing member to a recording material; fixing means for fixing an image onto the recording material, the fixing means including a heating member and back-up
15 roller for forming a nip cooperation with the heating member, in which the back-up roller has a conductive material containing layer; and in which a voltage applied to the transfer member when the recording material is a resin sheet is lower than a voltage
20 applied thereto when the recording material is paper.

Other objects of the present invention will be more apparent from the following detailed description with reference to the accompanying drawings.

25 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic view showing a configuration of an image forming apparatus in

10086156-02600

accordance with a first embodiment;

Fig. 2 is a schematic sectional view of a fixing apparatus;

Fig. 3 is a schematic view showing a
5 configuration of layers of a fixing film;

Fig. 4 is a schematic view showing a configuration of layers of a pressurizing roller;

Fig. 5 is a schematic view for illustrating a ground structure of the fixing film and the
10 pressurizing roller;

Fig. 6 is a graph showing a transfer bias output value; and

Fig. 7 is a schematic view showing a configuration of an image forming apparatus in
15 accordance with a second embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be hereinafter described with reference to the
20 accompanying drawings.

In addition, in the accompanying drawings, like reference numerals designate the same or similar parts throughout the figures thereof.

<First embodiment>

25 (1) Image forming apparatus

Fig. 1 is a schematic view showing a configuration of an image forming apparatus in

20250103100000

accordance with this embodiment. The image forming apparatus of this embodiment is a laser beam printer utilizing an electrophotographic process.

Reference numeral 1 denotes a drum-type
5 electrophotographic photosensitive body (hereinafter referred to as "photosensitive drum") as an image bearing member. The photosensitive drum 1 is rotatably supported by an apparatus main body M and is driven to rotate in an arrow R1 direction at a
10 predetermined process speed by driving means (not shown).

A charging roller (charging apparatus) 2, exposing means 3, a developing apparatus 4, a transfer roller (transferring apparatus) 5 and a
15 cleaning apparatus 6 are arranged in this order around the photosensitive drum 1 along its rotational direction.

In addition, a sheet feeding cassette 7 containing sheet-like recording materials P such as
20 paper is arranged in the lower part of the apparatus main body M. Above the sheet feeding cassette 7, a sheet feeding roller 15, a conveying roller pair 8, a top sensor 9, a conveying guide 10, a fixing apparatus (heating apparatus) 11, a conveying roller
25 pair 12, a sheet discharging roller pair 13 and a sheet discharging tray 14 are arranged in this order from an upstream side along a conveying path of the

20250320 09:22:00

recording material P.

The photosensitive drum 1 driven to rotate in the arrow R1 direction by the driving means is uniformly charged to a predetermined polarity and a
5 predetermined potential by the charging roller 2 to which a predetermined charging bias is applied from a not-shown charging bias power source.

After charging, the photosensitive drum 1 is subject to image exposure L on its surface based on
10 image information by the exposing means 3 such as a laser optical system. Then, charges on an exposed portion are removed from the photosensitive drum 1 and an electrostatic latent image is formed thereon.

The electrostatic latent image is developed by
15 the developing apparatus 4. The developing apparatus 4 has a developing roller 4a, applies a predetermined developing bias to the developing roller 4a from a not-shown developing bias power source and causes toner to adhere to the electrostatic latent image on
20 the photosensitive drum 1, thereby developing the electrostatic latent image as a toner image (visualization).

The toner image is transferred onto the recording material P such as paper by the transfer
25 roller 5. The recording material P is contained in the sheet feeding cassette 7, fed and conveyed by the sheet feeding roller 15 and the conveying roller pair

10082456-0260

8 and conveyed to a transfer nip portion that is a pressing-contact nip portion between the photosensitive drum 1 and the transfer roller 5 via the top sensor 9. At this point, a tip of the recording material P is detected by the top sensor 9 and is synchronized with the toner image on the photosensitive drum 1.

A predetermined transfer bias is applied to the transfer roller 5 by a transfer bias power source S at predetermined control timing, whereby the toner image on the photosensitive drum 1 is electrostatically transferred on the recording material P at a predetermined position. Reference numeral 31 denotes a control circuit (CPU) for controlling a transfer bias voltage outputted by the transfer bias power source S.

The recording material P with an unfixed toner image born on its surface by the transfer is separated from the surface of the photosensitive drum and conveyed to the fixing apparatus 11 along the conveying guide 10. In the fixing apparatus 11, the unfixed toner image is heated and pressurized to be fixed on the surface of the recording material.

The recording material P having been fixed with the toner image is conveyed by the conveying roller pair 12 and discharged onto the sheet discharging tray 14 on the upper surface of the apparatus main

1008156.02502

body M by the discharging roller pair 13.

On the other hand, after the toner image is transferred, toner which is not transferred and remains on the surface of the photosensitive drum 1 (transfer residual toner) is removed by a cleaning blade 6a of the cleaning apparatus 6. The photosensitive drum 1 prepares for the next image formation.

Images can be formed one after another by repeating the above operations.

(2) Fixing apparatus 11

Fig. 2 is a schematic sectional view of the fixing apparatus 11 in this embodiment. The fixing apparatus 11 of this embodiment is a heating apparatus of a pressurizing roller driving method and a film heating method disclosed, for example, in Japanese Patent Applications Laid-open Nos. 4-44075 to 44083.

This fixing apparatus 11 is composed of, as main constituent members, a ceramic heater (hereinafter referred to as "heater") 20 as a heating member for heating toner, a cylindrical fixing film 25 containing the heater 20, a pressurizing roller (back-up roller) 26 for forming a nip in cooperation with the heater 20 via the fixing film 25, temperature control means 27 for controlling a temperature of the heater 20, and rotation control

means 28 for controlling the conveyance of the recording material P.

The heater 20 consists of a resistor pattern 20b which is formed on a heat-resistant base material 20a
5 such as alumina by, for example, printing and which is coated with a glass layer 20c over its surface. The heater 20 is long in a right-left direction perpendicular to a conveying direction K of the recording material P, that is, formed to be longer
10 than the width of the recording material P. The heater 20 is supported by a heater holder 22 attached to the apparatus main body M.

The temperature control means 27 for controlling a temperature of the heater 20 includes a thermistor
15 (temperature detecting element) 21 attached to the back of the heater 20 and a CPU 23 for controlling a triac 24 based on a temperature detected by the thermistor 21 and also controlling conduction of the heater 20.

20 The heat holder 22 is a member formed in a semicircular shape on its cross section by heat-resistant resin and also acts as a guiding member for guiding rotation of the fixing film 25.

The fixing film 25 is heat-resistant resin such
25 as polyimide formed in a cylindrical shape and rotates around the heater 20 and the heater holder 22. The fixing film 25 is pressed against the heater 20

10032156 022602

by the pressurizing roller 26, whereby the back of the fixing film 25 is forced to abut the lower surface of the heater 20. The fixing film 25 is constructed so as to be rotated in an arrow R25 direction while the recording material P is conveyed in an arrow K direction by the rotation of the pressurizing roller 26 in an arrow R26 direction.

Further, both the left and right ends of the fixing film 25 are regulated so as not to slant to one side by a guide portion (not shown) of the heat holder 22 and are prevented from coming off in the longitudinal direction of the heater 20. In addition, grease is applied to the internal surface of the fixing film 25 in order to reduce its sliding resistance to the heater 20 and the heater holder 22.

Details of the pressurizing roller 26 will be described later. Briefly, a role of the pressurizing roller 26 is to press the fixing film 25 to the heater 20 upward by its outer circumference, thereby forming a fixing nip portion N between itself and the fixing film 25. Assuming that a width (nip width) of the pressurizing roller 26 in the rotational direction in this fixing nip portion N is a, the nip width a is set to a degree with which the toner on the recording material P can be preferably heated and pressurized.

The rotation control means 28 includes a motor

209220" 9572807
10082156 .022502

29 for driving the pressurizing roller 26 to rotate and a CPU 30 for controlling the rotation of the motor 29.

In the state in which the pressurizing roller 26 is driven to rotate, the fixing film 25 rotates following it and the conduction to the heater 20 is controlled to adjust the temperature of the fixing nip portion N to a predetermined fixing temperature, the recording material P bearing the unfixed toner image t is conveyed to the part of the fixing nip portion N between the fixing film 25 and the pressurizing roller 26 to be nipped and conveyed by the fixing nip portion N. As a result, the unfixed toner image t is heated by the heater 20 via the fixing film 25 and fixed by the heat. The recording material P that has passed through the fixing nip portion N is separated from the external surface of the fixing film 25 to be discharged and conveyed.

a) Fixing film 25

Fig. 3 is a schematic view showing a structure of layers of the fixing film 25. The fixing film 25 of this embodiment has a three-layer structure. An innermost layer is a base layer 25c, which takes mechanical property such as torsion strength and smoothness and is made of a resin such as polyimide. The next layer is a conductive primer layer 25a. The conductive primer layer 25a is a conductive layer in

10082156.022607

which conductive particles such as carbon black are dispersed and whose resistance is reduced, and assumes a role of an adhesive for joining a third layer 25b and the base layer 25c. An outermost layer is the top layer 25b. The top layer 25b is designed with a resistance value and a film thickness that are matched to property of toner used for the image forming apparatus and conditions for constructing the image forming apparatus.

b) Pressurizing roller 26

Fig. 4 is a schematic view showing a structure of layers of the pressurizing roller 26. The pressurizing roller 26 has a structure including only an elastic layer 26b on a core metal 26 or further including one or more resin layers 26d on the elastic layer 26b.

As the resin layer 26d, it is sufficient to provide a fluorocarbon resin layer or the like when high releasing property is required for the pressurizing roller 26 or, if necessary, provide a plurality of resin layers when surface property or the like is adjusted.

The pressurizing roller 26 of this embodiment is provided with a foaming silicone rubber as the elastic layer 26b on an aluminum core metal 26a. Then, after vulcanization and molding, an RTV silicone rubber, which has been subject to primary

10082156.022502

processing and has adhesion property, is applied to
the foaming silicone rubber as an adhesive layer 26c.
Moreover, an injection molded PFA tube is coated over
the RTV silicone rubber as the resin layer (releasing
5 layer) 26d.

Here, in the present invention, a resistance of
an elastic layer provided on a core metal or a
resistance one or more resin layers on the elastic
layer is adjusted to be 10^{13} Ω /sq or less in terms of
10 a surface resistance or 10^{11} Ω cm or less in terms of a
volume resistance by dispersing conductive particles
such as carbon black in these layers.

If the elastic layer provided on the core metal
or the resin layers have a surface resistance of 10^{13}
15 Ω /sq or more, since an electric resistance is too
large, triboelectrification generated between high
resistance paper (recording material) and a surface
of a pressurizing roller cannot be flown to the
ground. In this embodiment, carbon black is
20 dispersed in the RTV silicone rubber of the adhesive
layer 26c, whereby the surface resistance is adjusted
to 10^{10} Ω /sq. In addition, although the PFA tube of
the releasing layer 26d is an insulator, since its
film thickness is set at 20 μ m, a withstand voltage
25 of its surface can be kept low (approximately 2 kV or
less) and charges generated on the surface of the
pressurizing roller 26 by friction with the recording

10082156 022602

material P can be flown to the resistance-adjusted adhesive layer 26c immediately below the resin layer 26d.

c) Ground structure of the pressurizing roller 26

5 As shown in Fig. 5, in a recording material non-passing area on one side end in the longitudinal direction of the fixing film 25 and the pressurizing roller 26 that are pressured to contact each other to form the fixing nip portion N, the releasing layer
10 26d of the pressurizing roller 26 is not provided and the adhesive layer 26c is exposed to the surface. Similarly, the conductive primer layer 25a of the fixing film 25 is also exposed in the recording material non-passing area. Thus, the adhesive layer
15 26c of the pressurizing roller 26 and the conductive primer layer 25a of the fixing film 25 contact each other to be electrically conducted. In addition, a conductive brush 32 is caused to contact the external surface of the exposed part of the conductive primer
20 layer 25a of the fixing film 25, whereby the conductive brush 32 is grounded.

Therefore, charges generated on the surface of the pressurizing roller 26 by friction with the recording material P are flown to the resistance-
25 adjusted adhesive layer 26c immediately below the resin layer 26d. The charges are further flown to the ground via the conductive primer layer 25a of the

40082156 "022502"

fixing film 25 and the conductive brush 32.

(3) Transfer bias control

Next, details of transfer bias control characterizing the present invention will be
5 described.

As described above, a toner image on the photosensitive drum 1 is electrostatically transferred onto the recording material P by a transfer bias applied to the transfer roller 5.

10 Usually, the transfer bias is appropriately set according to a resistance value of a member used for the transfer roller 5 and an environment in which the image forming apparatus is used. In this embodiment, the image forming apparatus has an exclusive mode
15 (OHT mode) in passing an OHT (resin sheet) as a recording material. If the OHT mode is selected by an input from a host computer or a direct input to the image forming apparatus, the control circuit 31 (Fig. 1) sets an output of a transfer bias from the
20 transfer bias power source S to the transfer roller 5 lower than that in a normal operation (a mode in which plain paper is passed to be used as a recording material, i.e., a plain paper mode).

For example, the image forming apparatus of this
25 embodiment causes an output of a transfer voltage to change according to a resistance value of a transfer roller as shown in Fig. 6 in the normal operation.

However, if the OHT mode is selected as opposed to this normal operation, an output value of a transfer voltage of the transfer bias power source S controlled by the transfer bias control circuit 31 is
5 set to be one third of that in the normal operation. Note that a transfer bias value with respect to a transfer roller resistance in the image forming apparatus of this embodiment is determined based on a voltage value at the time when the transfer bias is
10 outputted at a constant current before feeding a recording material. In addition, although the transfer bias in the OHT mode is set at one third of that of the plain paper mode in this embodiment, offset that occurs when the OHT is used can be
15 prevented if this ratio is in a range from 3% to 80%.

As described above, the pressurizing roller 26, which has been subject to treatment for lowering resistance, inevitably generates an offset image when an OHT is passed. However, if a transfer bias
20 applied to the back of the OHT is small in a transfer portion, negative charges induced on the surface of the OHT become small proportionate to the transfer bias. Therefore, even if transfer charges on the back of the OHT flow to the ground via the
25 pressurizing roller 26, repulsion between toner and the negative charges becomes weaker than that in the case where a normal transfer bias is applied, and

10082156.022602

reduction of a holding power of the toner can be kept low. As a result, occurrence of an offset image can be prevented.

5 A lower limit value of a transfer bias applied
to a transfer roller is set such that an unfixed
toner image that is transferred to a recording
material and held thereon does not scatter if a high
resistance recording material is used. This is
because, if the transfer bias is too small, charges
10 required for holding the toner image on the recording
material become insufficient and the toner image
scatters immediately after passing through a transfer
position. Therefore, it is necessary to set the
transfer bias at a value that does not cause such
15 scattering of the toner image.

When a recording material is an OHT, since the
OHT has a high resistance, scattering of a toner
image tends to occur if a transfer bias is small.
However, since an image formed on the OHT is
20 recognized by human eyes when it is projected by a
projector, a little scattering of an image is hardly
recognized by human eyes. Thus, a slight margin may
be allowed for the lower limit value of the transfer
bias. Nevertheless, since significant reduction of
25 the transfer bias leads to scattering of an image at
an unacceptable level even on the OHT, it is
necessary to appropriately set the transfer bias

10082156 022602

according to an ability of a transferring apparatus
of the image forming apparatus. Thus, an output of
the transfer bias in the OHT mode is set at one third
of that in the normal operation. However, if the
5 transfer bias in the OHT mode is set in the range of
3% to 80% of that of the plain paper mode as
described above, scattering of an image can be kept
with an appropriate level when the OHT is used.

Results of measuring occurrence of an offset
10 image and potentials on the front and the back of an
OHT immediately before the OHT is fed in the fixing
apparatus are shown in Table 1. The measurement was
performed using the image forming apparatus of this
embodiment (1) when the OHT mode was selected by
15 direct input and (2) when the OHT mode was not
selected (as comparison).

Table 1

	Transfer bias value	Potential of the front of the sheet	Potential of the back of the sheet	Offset
(1) OHT mode	+ 900 V	- 400 V	+ 300 V	Good
(2) Normal mode	+ 2700 V	- 1300 V	+ 1000 V	Fail

As shown in Table 1, when the OHT mode was
selected to form an image on an OHT, negative charges
on the front of a sheet were small at -400 V and an
offset image did not occur. On the other hand, if
the normal mode was continued to form an image on the

OHT, the negative charges on the front of the sheet were large at -1300 V, the difference in absolute value between potentials of the front and the back of the sheet was also large at 300 V, and an offset
5 image occurred.

<Second embodiment>

As shown in Fig. 7, an image forming apparatus of this embodiment includes an optical sensor 16 (a
10 16b) as OHT detecting means between the top sensor 9 and a transfer portion. The image forming apparatus can detect whether or not the passed and used recording material P is an OHT by checking transparency of the recording material P.

15 Detection information of the optical sensor 16 as the OHT detecting means is inputted in the control circuit 31. When feeding of the OHT is detected, the control circuit 31 controls and sets an output value of a transfer voltage from the transfer bias power
20 source S to the transfer roller 5 to be one third of that in the normal operation.

Since the other control of the transfer bias and configuration of the image forming apparatus are the same as those in the first embodiment, repeated
25 descriptions are omitted.

The image forming apparatus of this embodiment has the same effect of preventing offset on an OHT as

40082156, 022650
2022092807

the image forming apparatus of the first embodiment.
However, whereas, in the image forming apparatus of
the first embodiment, the OHT mode is selected by a
direct input to the apparatus or by an input from a
5 host computer, in the image forming apparatus of this
embodiment, the OHT mode is selected by the image
forming apparatus itself detecting the OHT. As a
result, occurrence of an offset image due to failure
to select the OHT mode can be prevented.

10 <Other embodiments>

1) In the transferring apparatus 5, a transfer
member of a form such as a transfer belt or a
transfer blade can be used as a contact type transfer
member other than the transfer roller.

15 2) The fixing apparatus 11 is not limited to the
heating apparatus of the pressurizing roller driving
method and the film heating method of the first
embodiment and may be any heating apparatus such as
that of the heat roller method or an electromagnetic
20 induction heating method. It may also be a pressure
fixing apparatus.

Thus, it is seen that an image forming apparatus
having a transfer bias control function is provided.
One skilled in the art will appreciate that the
25 present invention can be practiced by other than the
preferred embodiments which are presented for the
purposes of illustration and not of limitation, and

2025 RELEASE UNDER E.O. 14176

the present invention can be modified in any way within the technical thoughts of the present invention.

1082156.022602